TEST UNIT AND EQUIPMENT:

CU20029-KTW220A prototype was tested between 26-Nov and 29-Nov, 2007.

Weiss WKL 100 Environmental Chamber serial 2200299200 calibrated 14-Aug-2007. Shaffner NSG435 ESD simulator PA0138 uncalibrated.

Agilent E4402B spectrum analyser PA0193 calibrated 9-Nov-2007.

OPERATING CONDITION:

VCC = 5V, GND = 0V Module powered in Self Test mode

TEMPERATURE RANGE:

The module was brought to temperature in the Weiss-Technik chamber in the sequence, and for the durations shown. Module was stabilised for 30 minutes at each operating temperature before being powered on in self-test mode, and visual quality of display observed.

| Temp | Duration | Observation |
|------|----------|--------------------|
| -40C | 19 hours | Off, storage |
| -10C | 1 hour | Operating, OK |
| +85C | 7 hours | Operating, storage |
| +65C | 1 hour | ОК |

ELECTRO-STATIC DISCHARGE (Method IEC 6100-4-2):

The module was powered up in self-test mode on the test table. There it was exposed to contact and air discharges applied to the ribbon cable across the module face, the horizontal conductive plane under the module, and the vertical conductive plane.

| Observation | Contact Discharge | Air Discharge |
|-------------------------------------|-------------------|---------------|
| Lowest voltage discharged | 1kV | 2kV |
| Temporary spurious ON/OFF of pixels | 5kV | None |
| Module reset or lock-uo | None | None |
| Permanent damage | None | None |
| Highest voltage discharged | 9kV | 16kV |

CONDUCTED RF EMISSION TEST:


The 50-ohm input of the Agilent E4402B spectrum analyser was AC-coupled to the 5V supply of the module.


While the module performed self-test, the spectra shown overleaf were taken:


| Start | Stop | Spectra | Significant UUT peaks |
|---------|----------|-----------------|-----------------------|
| 50 kHz | 2050 kHz | UUT | -57dBm @80kHz |
| 1 MHz | 11 MHz | UUT | None |
| 8 MHz | 88 MHz | UUT | -40dBm @27MHz |
| 80 MHz | 280 MHz | UUT, background | None above -50dBm |
| 0.2 GHz | 3 GHz | UUT | None above -50dBm |


Environmental Test


CU20029-KTW220A











CONTACT

Noritake Sales Office Tel Nos Nagoya Japan: +81 (0)52-561-9867 Canada: +1-416-291-2946 Chicago USA: +1-847-439-9020 Munchen (D): +49 (0)89-3214-290 Itron UK: +44 (0)1493 601144 Rest Europe: +49 (0)61-0520-9220 www.noritake-itron.com

Subject to change without notice. IUK Doc Ref: 10847 lss:1 18Feb08